



# **SUMMARY**

#### # Wires

 Low
 0

 High
 0

 Coax
 0

 Triax
 0

**Quad** 0 **Fiber** 0

Fluidic 0

Series 1M

Termination type No contacts / Accessory

IP rating 50

**Cable Ø** 0.00 - 0.00 mm

**Matching parts** 

**Status** active

Alternative part



Image is for illustrative purpose only

#### **Download**

Request a quote

Catalog

# **TECHNICAL DETAILS**

#### **Mechanics**

Shell Style/Model BGE\*: Blanking cap for fixed receptacle (arctic grip)

Keying

Housing Material Environment friendly aluminium (nickel plated, anthracite color) shell and nut, other pieces

bronze/brass

Cable Fixing : 0 - 0 mm

**Variant** 

#### **Performance**

Configuration

Insulator

**Rated Current** 

#### **Specifications**

Contact LEMO for performance details.

#### **Others**

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

Humidity (max): <=95% [at 60 deg C /140 F]

Vibration: 15 g [10 Hz - 2000 Hz] Shock Resistance: 100 g [ 6 ms]


Operating temperature: -55°C/ +200°C Climatical Category: 15/200/21 (Al. shell) Lighting strike EIA 364-75 10K amps - 6 times

EMI Shielding EIA 364-66A - 1Ghz-80 dB,3GHz-70 dB,6GHz- 58dB

IP Rating: 50

## **DRAWINGS**

#### **Draws**



#### **Dimensions**

	А	С	L	N	Р	Х
mm.	15.9	14.2	23.4	85	3.9	6
in.	0,63	0,56	0,92	3,35	0,15	0,24

# **RECOMMENDED BY LEMO**

#### **Tools**

None

### **Cables**

121 221		

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.

131 221 151 221		
161 221		

LEMO products and services are provided "as is". LEMO makes no warranties or representations with regard to LEMO product & services or use of them, express, implied or statutory, including for accuracy, completeness, or security. The user is fully responsible for his products and applications using LEMO components.