

**Mechanical characteristics**

interface dimensions acc. to panel piercing  
 centre conductor  
 outer conductor  
 mating life  
 coupling torque

**Components**

centre contact  
 outer contact  
 other metal parts  
 insulator  
 insulating washer  
 gasket

**Electrical characteristics**

impedance  
 frequency  
 voltage proof  
 insulation resistance  
 contact resistance  
 centre contact  
 outer contact

**Environmental**

barrier sealing  
 RoHS compliant

**Mechanische Eigenschaften**

Steckgesicht nach Montagebohrung  
 Innenleiter  
 Außenleiter  
 Steckzyklen  
 Kupplungsdrehmoment

**Bauteile**

Innenkontakt  
 Außenkontakt  
 sonstige Metallteile  
 Isolierung  
 Isolierscheibe  
 Dichtung

**Elektrische Eigenschaften**

Wellenwiderstand  
 Frequenz  
 Spannungsfestigkeit  
 Isolationswiderstand  
 Durchgangswiderstand  
 Innenkontakt  
 Außenkontakt

**Umgebung**

Längsdichtigkeit  
 RoHS konform


IEC 60169-17  
 Z051  
 solder/ löt  
 solder/ löt  
 >500  
 0,46-0,69 Nm

**Materials / Material**  
 CuBe2Pb  
 CuZn38Pb2  
 CuZn39Pb3/CuSn6  
 PTFE  
 PC transparent  
 silicone / Silikon

**Finish / Oberfläche**  
 (a) NiP Au  
 Cu2Ni5  
 Cu2Ni5

50 Ω  
 0-11 GHz  
 1.5 kV<sub>eff</sub> / 50 Hz  
 ≥ 5 MΩ  
 ≤ 10 mΩ  
 ≤ 2.5 mΩ

IP 67 (IEC 60529)  
 2002/95/EC

α	24609	14.02.13	MA	2012	Datum/ date	Name/ name	Gewicht/ weight [g]	Oberfläche/ surface [mm <sup>2</sup> ]	Werkstoff/ material
				gez./ drawn	08.08.	MA			
				gepr./ appr.	08.08.12	BJ			Oberfläche/ finish
				Norm/ stand.					
				Maßstab/ scale	Benennung/ title				
				2:1	TNC Bulkhead Socket TNC-Einbaubuchse				
				untol. Maße/ dim. without tolerances according to	Untert./doc. type	Zeichnungsnr./ drawing no.			
				K	J01011A0013				
									 Maße/ dimensions: mm
									Original : DIN A4
									Blatt/ sheet 1 von/ of 1