



Through/Ground Conductor/Shield Conductor/Ex Terminal Block TOPJOB® S; 6 (10) mm²; 2006 Series

Technical Data	
0.5 ... 6 (10) mm ² ①	20 ... 8 AWG
800 V/8 kV/3 ②	600 V, 50 A ③
I _N 41 A (57 A)	600 V, 50 A ④
Terminal block width: 7.5 mm / 0.295 inch	
13 ... 15 mm / 0.51 ... 0.59 inch	



Technical Data	
0.5 ... 6 (10) mm ² ①	20 ... 8 AWG
800 V/8 kV/3 ②	600 V, 50 A ③
I _N 41 A (57 A)	600 V, 50 A ④
Terminal block width: 7.5 mm / 0.295 inch	
13 ... 15 mm / 0.51 ... 0.59 inch	



- ① Conductor range: 0.5 ... 10 mm² "s+f-st"
Push-in termination: 1 ... 10 mm² "s"
and 1.5 ... 6 mm²
"insulated ferrules, 12 mm"
 - ② 800 V = rated voltage
8 kV = rated impulse voltage
3 = pollution degree
 - ③ Terminal blocks with a blue insulated housing are suitable for Ex i applications.
 - ④ Terminal blocks with an Ex mark are suitable for Ex e II applications.
550 V; 38 A; for 2-conductor terminal blocks
550 V; 36 A; for 3-conductor terminal blocks
33 A jumper
- " Please observe the application notes:
Separator for Ex e/Ex i applications, see page 29
Step-down jumpers, see page 41
Jumpers, from page 149
Testing accessories, from page 142
Marking, from page 230

2-conductor through terminal block		
Color	Item No.	Pack. Unit
gray ⑤	2006-1201 ④	50
blue ⑤	2006-1204 ③ ④	50
orange ⑤	2006-1202 ④	50

3-conductor through terminal block		
Color	Item No.	Pack. Unit
gray ⑤	2006-1301 ④	25
blue ⑤	2006-1304 ③ ④	25
orange ⑤	2006-1302 ④	25

2-conductor ground terminal block		
green-yellow ⑤	2006-1207 ④	50

3-conductor ground terminal block		
green-yellow ⑤	2006-1307 ④	25

2-conductor shield terminal block		
white	2006-1208	50

Accessories; item-specific			
End and intermediate plate; 1 mm thick			
orange	2006-1292	100 (25)	
gray	2006-1291	100 (25)	

Accessories; item-specific			
End and intermediate plate; 1 mm thick			
orange	2006-1392	100 (25)	
gray	2006-1391	100 (25)	

Separator; oversized; 2 mm thick			
orange	2006-1294	100 (25)	
gray	2006-1293	100 (25)	

Separator; oversized; 2 mm thick			
orange	2006-1394	100 (25)	
gray	2006-1393	100 (25)	

Accessories; 2006 Series

Appropriate marking systems: WMB/WMB Inline/Marking Strips

Ex e/Ex i separator; orange; 3 mm thick			
120 mm	209-191	50 (25)	

Lockout cap; for conductor entry and operating slot			
gray	2006-191	25	

Push-in type jumper bar; insulated; I _N 41 A; light gray			
2-way	2006-402	25	
3-way	2006-403	25	
4-way	2006-404	25	
5-way	2006-405	25	

Modular TOPJOB® S connector; snaps together; for jumper contact slot			
gray	2006-511	50 (25)	

Push-in type jumper bar; insulated; I _N 41 A; light gray			
1 to 3	2006-433	25	
1 to 4	2006-434	25	
1 to 5	2006-435	25	

Test plug adapter; for 4 mm Ø test plug			
gray	2009-174	100 (25)	

Star point jumper; insulated; I _N = I _N terminal block; light gray			
1-3-5	2006-405/011-000	25	

Marking strip; plain; 11 mm wide; 50 m reel			
white	2009-110	1	

Step-down jumper; insulated; commons 6/4 mm ² (10/12 AWG) to 4/2.5/1.5 mm ² (12/14/16 AWG); I _N 32 A			
light gray	2006-499	25	

WMB Multi marking system; white; 10 strips with 10 markers/card; stretchable from 5 ... 5.2 mm			
plain	793-5501	5	

Protective warning marker; with black high-voltage symbol; for 5 terminal blocks			
yellow	2006-115	100 (25)	



Cover (2006-191) seals unused conductor entry.



Commoning with Step-Down Jumpers