

Sleeving Braids - Tinned Copper on Former

Reference (equivalent to Ray 90)	I/D mm	Minimum Optical Coverage	Useable Range		Braid Specification	Cross Sectional Area - sqmm	Weight kg/100m	Packing Unit m
			Min Dia mm	Max Dia mm				
HUB 3.0	3	90%	2.00	3.50	16/5/0.13	1.06	1.0	100
HUB 4.0	4	90%	3.00	5.00	16/7/0.13	1.49	1.45	100
HUB 5.0	5	90%	4.00	6.00	24/6/0.13	1.91	1.85	100
HUB 6.0	6	90%	5.00	7.00	24/7/0.13	2.23	2.20	100
HUB 10.0	10	90%	7.00	12.00	24/9/0.16	4.34	4.20	50
HUB 12.5	12.5	90%	11.00	13.00	24/10/0.16	4.83	4.80	50
HUB 15.0	15	90%	13.00	18.00	24/11/0.20	8.29	8.30	50
HUB 20.0	20	90%	17.00	23.00	48/10/0.16	9.65	9.60	50
HUB 25.0	25	90%	22.00	28.00	48/13/0.16	12.54	12.50	50
HUB 30.0	30	90%	27.00	36.00	48/20/0.16	19.30	19.20	25
HUB 35.0	35	90%	30.00	50.00	48/20/0.16	19.30	19.30	25
HUB 50.0	50	90%	45.00	65.00	36/14/0.30	4.90	42.00	25

Reference (equivalent to Ray 101)	I/D mm	Minimum Optical Coverage	Useable Range		Braid Specification	Cross Sectional Area - sqmm	Weight kg/100m	Packing Unit m
			Min Dia mm	Max Dia mm				
HUB 95 3.0	3	95%	2.00	5.00	16/10/0.10	1.23	1.25	100
HUB 95 4.0	4	95%	3.50	7.50	24/7/0.13	2.23	2.20	100
HUB 95 6.0	6	95%	4.50	9.50	24/9/0.13	2.87	2.80	100
HUB 95 7.5	7.5	95%	7.00	14.00	24/14/0.13	4.47	4.40	100
HUB 95 10.0	10	95%	8.00	22.00	36/12/0.13	5.73	5.70	50
HUB 95 12.5	12.5	95%	11.00	24.00	36/15/0.13	7.16	7.50	50
HUB 95 20.0	20	95%	16.00	38.00	48/16/0.13	10.21	10.00	50
HUB 95 25.0	25	95%	22.00	38.00	48/18/0.13	11.49	11.25	50
HUB 95 30.0	30	95%	27.00	40.00	36/18/0.20	20.36	20.30	25