

Illuminated pushbutton, Series 82, Ø 22 mm, flush, Silver, IP65, IP67, Plug-in terminal, 2.8 x 0.5 mm

82-5151.2124



<https://eao.com/p/c18b7176>

Your product:

---



82-5151.2124

Illuminated pushbutton, Series 82, Ø 22 mm, flush, Silver, IP65, IP67, Plug-in terminal, 2.8 x 0.5 mm

#### PRODUCT RANGE

**HMI function:** Illuminated pushbutton  
**Series:** Series 82

#### FRONT

**Front dimension:** Ø 22 mm  
**Front bezel colour:** Silver  
**Front bezel material:** Stainless steel

#### MOUNTING

**Design:** flush  
**Mounting cut-out:** Ø 19 mm

#### OPERATING-/INDICATION PART

**Shape of illumination:** Ring  
**Lens illumination:** illuminative  
**Lens colour:** Silver  
**Lens shape:** flush  
**Lens material:** Stainless steel  
**Illumination colour:** Blue

#### ELECTRICAL CHARACTERISTICS

**Electrical lifetime:** 50 000 cycles of operation

**Switching voltage and switching current:**

according to IEC 60947-5-1 (Silver contacts)	
Service categorie AC-15	
Voltage	Current
24 VAC	1 A
35 VAC	1 A (M12 versio
110 VAC	1 A
220 VAC	0.5 A
Switch rating DC service categorie DC-13 (Silver contacts)	
Voltage	Current
24 VDC	0.7 A
35 VDC	0.5 A (M12 vers
110 VDC	0.2 A
220 VDC	0.1 A

according to UL 508 (Silver contacts)	
cosφ 0,75 ... 0,8	
Voltage	Current
120 VAC	5 A
240 VAC	3 A
24 VAC	1 A

<b>Lumi. Intensity:</b>	mcd
<b>Operating voltage:</b>	24 V AC/DC ±10 %
<b>Operation current:</b>	7 mA

**MECHANICAL CHARATERISTIC**

<b>Tightening torque:</b>	Fixing nut 0.5 Nm min. ... 1.2 Nm max., Screw terminal 0.1 Nm
<b>Terminal:</b>	Plug-in terminal, 2.8 x 0.5 mm
<b>Contact material:</b>	Silver
<b>Switching action:</b>	Maintained
<b>Switching system:</b>	Snap-action switching element
<b>Total weight:</b>	0.018 kg

**AMBIENT CONDITION**

<b>IP front protection:</b>	IP65, IP67
<b>Operating temperature:</b>	- 30 °C ... + 70 °C
<b>Storage temperature:</b>	- 40 °C ... + 80 °C

**OTHER**

<b>max. number of switching elements:</b>	1
<b>Housing colour:</b>	Silver
<b>Housing material:</b>	Stainless steel

<b>Gehäuse Grösse:</b>	19 mm
<b>Symbol:</b>	no symbol
<b>Article number:</b>	82-5151.2124